CCAM Cable

COPPER CLAD ALUMINIUM MAGNESIUM CABLE

A cable designed by CQR to meet all aspects of the European Construction Product Regulation (CPR) EN50575.

This cable has been independently tested and certified by an accredited test facility and has been awarded a CPR Euro classification.

CQR offer the Installer, Specifier and End User a quality cabling solution and piece of mind that the product will perform to specification in the event of a fire.

DoP Certificates available online for download







- Suitable for domestic applications and shorter distances
- 7 x 0.2mm Copper Clad Aluminium
- Type 1 PVC Jacket
- Screened or Unscreened
- Manufactured to BS4737-3.30:2015 Type 3
- Fully compliant with EN50575 'CPR'

Available Cores



Product codes Technical data Code Description Core: 7 x 0.2mm 4 Core CCA White 100mtrs Resistance: 147.9 Ohms/Km CABCCA6/WH/100M Conductor Material: Tinned Copper Clad Aluminium Magnesium CABCCA8/WH/100M 8 Core CCA White 100mtr Conductor area: 0.22mm² CABCCA12/WH/100M 12 Core CCA White 100mtrs AWG: 24 CABCCAS4/WH/100M ened CCA White 100 CABCCAS6/WH/100M 6 Core Scr ed CCA White 100mtrs Max voltage: 50 volts CABCCAS8/WH/100M 8 Core Screened CCA White 100mtrs Sheathing: PVC CABCCAS12/WH/100M 12 Core Sc ened CCA White 100mt Core insulation: *PVC* Operating temp: 70°C Other cable lengths and colour available Euroclass Rating: Euroclass See www.cqr.co.uk for details SCREENED CABLE in Drain wire: Soft tinned copper www.cqr.co.uk Screen: Alu/Polyester Foil Over 30 Years experience of alarm cable manufacturing in the United Kingdom



Tech: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK





