

## **DS-1200KI Series Network Keyboard**

**Features and Functions** 

- 128 x 64 screen
- 4-axis joystick
- Connectable to the Multi-functional Video Center (MVC), Matrix Access Gateway (MAG), Video Wall Controller, Decoder, etc.; and shortcut operation of camera/camera groups switch on video wall
- Connectable to dome and realize PTZ control and picture capture by joystick operation
- Connectable to DVR via network or serial port, and operation of front panel buttons
- 16 user accounts management: 1 admin and 15 operators
- System upgrade and import / export of configuration files by USB-flash disk
- Captured pictures(FAT32) can be stored in U-flash disk
- Network access and configuration by Web browser support; and up to 1000 devices can be managed in the keyboard operation mode





| Specifications         |                                      |   |
|------------------------|--------------------------------------|---|
| Model                  |                                      | DS-1200KI   |
| System                 | LCD screen                           | 128 x 64 pixel screen                             |
|                        | Joystick                             | 4-axis joystick                                   |
|                        | Control mode                         | Network, RS-232, RS-422, RS-485                   |
| External<br>Interfaces | Network interface                    | 1; 10 M/100 Mbps self-adaptive Ethernet interface |
|                        | Serial interface                     | 1 RS-232, 1 RS-422, 1 RS-485                      |
|                        | USB interface                        | 1 × USB 2.0                                       |
| General                | Power supply                         | 12 VDC  |
|                        | Consumption                          | ≤ 4.5 W   |
|                        | Working temperature                  | -10 to +55°C (14 to 131°F)                        |
|                        | Working humidity                     | 10% to 90%  |
|                        | Dimensions ( $W \times D \times H$ ) | 435 × 193 × 110 mm (17.1 × 7.6 × 4.3 inch)        |
|                        | Weight                               | ≤ 1 kg (2.2 lb)                                   |

## **Available Models**

## DS-1200KI

Distributed by

Г



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Africa T +27 (10) 0351172 sale.africa@hikvision.com Hikvision Europe T +31-23-55-42-770 info.eu@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Oceania T +61-2-8599-4233 salesau@hikvision.com

Hikvision Hong Kong T +852-2151-1761 Hikvision Middle East T +971-4-8816086 salesme@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Canada T +1-909-895-0400 sales.usa@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Poland T +48-22-460-01-50 poland@hikvision.com

Hikvision Korea T +82-31-731-8841 sales.korea@hikvision.com Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision UK T +01628-902140 support.uk@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2016 | Data subject to change without notice | 010000160100